





P.O. DRAWER 330 - DUNKIRK, MD 20754 USA TOLL FREE: (800) 368-2573 (USA & CANADA) TEL (301) 855-8300 - FAX (410) 257-7579 WEB SITE: HTTP://WWW.VICTORSTANLEY.COM

\*ALL DIMENSIONS ARE IN MILLIMETERS\*









LID SECURED WITH VINYL COATED GALVANIZED STEEL AIRCRAFT CABLE.

AND CRIMPED IN PLACE. (MOUNTING MAY VARY BETWEEN RECEPTACLES)

CABLE IS LOOPED AROUND WELDED IN PLACE ATTACHMENT BRACKETS

SECURITY

## AVAILABLE OPTIONS:

POWDER COATING

12 STANDARD COLORS, CUSTOM COLORS (INCLUDING THE RAL RANGE) CUSTOM DECALS

AVAILABLE WITH PRESSURE SENSITIVE VINYL OUTDOOR DECALS.
ASHTRAY

AVAILABLE WITH STAINLESS STEEL ASHTRAY.

## MATES

- 1. DRAWINGS NOT TO SCALE, DO NOT SCALE DRAWINGS.
- 2. ALL FABRICATED METAL COMPONENTS ARE STEEL SHOTBLASTED, ETCHED, PHOSPHATIZED, PREHEATED, AND ELECTROSTATICALLY POWDER-COATED WITH T.G.I.C. POLYESTER POWDER COATINGS. PRODUCTS ARE FULLY CLEANED AND PRETREATED, PREHEATED AND COATED WHILE HOT TO FILL CREVICES AND BUILD FILM COATING. COATED PARTS ARE THEN FULLY CURED TO COATING MANUFACTURER'S SPECIFICATIONS. THE THICKNESS OF THE RESULTING FINISH AVERAGES 8-10 MILS (200-250 MICRONS).
- 3. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE. CONTACT MANUFACTURER FOR DETAILS.
- 4. THIS PRODUCT IS SHIPPED FULLY ASSEMBLED.

## S-2E SPECIAL SPECIAL TOP LOAD RECEPTACLE LID (ENORY LID)